

Model ZOLID.PANEL

The **ZOLID.PANEL** is a powerful **All-in-One** ThinClient with **Touch-Display**.

Its robust design enables it to be used in production and logistics.

With an optionally available wall or Vesa mount, the Touch-ThinClient can be used on machines for process data acquisition and visualization. The Intel i5 processor family guarantees great computing power.

The openthinclient® model boots in connection with central administration by the **Management Server** * **via network (PXE)**. By using the onboard already integrated SSD, the ThinClient can - after the corresponding configuration in the management software * - can also be booted locally.

*ThinClient is delivered without an operating system and management software



Technical specifications

 **CPU**
Intel® Core™ i5 processor
11th Gen up to 4.50 GHz

 **RAM**
6 GB, DDR4 SO-DIMM
(max. 32 GB)

 **Graphics / display**
Chip: Intel® Iris® Xe Graphics
Display size: 21,5" TFT LCD
Resolution: 1920×1080
Color depth: 16,7 Mio
Surface: Anti-Glare
(anti-reflective coating)
Brightness: 250 nits
Touch function: capacitive
touch screen

 **LAN**
10/100/1000 MBit/s
supports PXE-Boot (UEFI)

 **Audio**
1× Mic-in
1× Line-out

 **Connections**
2× USB (3.0)
2× Ethernet RJ45
1× HDMI
1× VGA
1× Com

 **Power supply**
12V DC-IN

 **Performance**
approx. 22-35 watts

 **Measurements and weight**
554mm×355mm
(H×B without stand)
9 kg

 **Cooling**
Fanless

 **Surroundings**
-10° to 60° ambient temperature
in operation
10% - 90% humidity

 **Guarantee**
24 months Bring-in (B2B)

 **Certification mark**
CE, FCC, RoHS, ISO

 **Accessories (included)**
external power supply
prim. 110-240V~ @ 50/60 Hz

 **Accessories (optional)**
Stand
Vesa mount
Keyboard, Mouse
Warranty extension
to 36, 48, 60 months

 **Recommended thin client software**
openthinclient OS, from version 2025.x

 **Note**
Device dissipates the developed heat
via the housing. A cover can lead to
damage.