## open \*\* thinclient®

## Model ZOLID.SLAB



The ZOLID.SLAB is powered by an Intel® Celeron® processor, providing powerful performance for demanding applications. Additionally, it features three HDMI 2.0 interfaces, allowing for easy and fast use with multiple displays.

The fanless design produces no noise, making it ideal for production and office workstations.

The openthinclient® model boots in connection with central administration by the **Management Server** \* via network (PXE). By using the onboard already integrated SSD, the ThinClient can - after the corresponding configuration in the management software \* - can also be booted locally.

\*ThinClient is delivered without an operating system and management software

## **Technical specifications**

CPU
Intel® Celeron® up to 2.60 GHz

8 GB DDR4 SO-DIMM (max. 32 GB)

Graphics / display
Intel® UHD Graphics 10th Gen

**LAN**RTL8111H RJ45
10/100/1000 Mbps

Realtek HD

1× Mic-in

1× Line-out

Connections
1× SIM

2× LAN

4× USB (2.0)

2× USB (3.2) 1× USB-C

3× HDMI2.0 1× COM Intern 1× M.2 2280 NVMe SSD

1× M.2 2280 NVMe SSD 1× M.2 2242/2280 SATA SSD

Power supply
12V DC-IN

Performance approx 10 watt

Measurements and weight
191mm × 151mm x 34mm (H×BxT)
1,03 Kg

Cooling Fanless

Surroundings
-20°C to 60°C
Ambient temperature
in operation

**Guarantee** 24 months Bring-in (B2B)

Certification mark
CE, RoHS, LVD

Accessories (included)
external power supply
VESA mount

Warranty extension to 36, 48, 60 months

Recommended thin client software openthinclient OS, ab Version 2022.x

Note

Device dissipates the developed heat via the housing. A cover can lead to damage.