

Model BLACK.DOMINO /1


The **BLACK.DOMINO /1** is a compact and powerful ThinClient, excellently suited for both office use and deployment in clinics.


Equipped with the Intel® Celeron® Processor J, the **BLACK.DOMINO /1** delivers **robust computing power** with **low energy consumption** and ensures silent operation and low maintenance due to its fanless design. Fitted with two DisplayPorts, an elegant casing, and an additional stand, the client offers considerable versatility.

In conjunction with central management by the **openthinclient Management Server***, the openthinclient® model boots **via network (PXE)**. By using the locally integrated flash memory, the ThinClient - after the corresponding configuration in the management software* - **can also be booted locally**.


*ThinClient is delivered without an operating system and management software


Technical specifications


 **CPU**
Intel® Celeron® Processor J
2.00 GHz


 **RAM**
8 GB, DDR4 SO-DIMM
(max. 16 GB)


 **Graphics / display**
Intel® UHD Graphics for Intel® Core™ Processors 10th Gen.
2 x DisplayPort
up to 3840 x 2160 @ 60 Hz

 **LAN**
1 x Ethernet RJ45
10/100/1000 MBit/s
supports PXE-Boot (UEFI)


 **Audio**
1 x 3.5mm Headset
(-support -TRRS)
1 x built-in
0.5 W Speaker


 **Connections**
2 x USB (3.2 Gen. 1)
4 x USB (2.0)


 **Intern**
1 x mSATA


 **Local memory**
1 x 32 GB eMMC

 **Power supply**
12V DC-IN


 **Performance**
approx. 10 watt


 **Measurements and weight**
Plastic casing,
black, vertical
200 mm x 40 mm x 150 mm (HxWxD)
1020 g


 **Cooling**
Fanless, passively cooled


 **Surroundings**
0° - 35° Ambient temperature
In operation
20% - 80% Humidity


 **Guarantee**
24 months Bring-in (B2B)

 **Certification mark**
CE, FCC, LVD

 **Accessories (included)**
external power supply
100-240V@ 50-60 Hz
Stand
VESA mount

 **Accessories (optional)**
Warranty extension to
36, 48, 60 months
Wi-Fi Module
Fiber Optic LAN
TPM 2.0
Keyboard, Mouse

 **Recommended thin client software**
openthinclient OS, from version 2022.x

 **Note**
Device dissipates the developed heat via the housing. A cover can lead to damage.